

# CleanCode EV1 & EV2 LX

HIGH RESOLUTION THERMAL INK JET CODERS



## FEATURES

- ▶ Easy to operate
- ▶ Ready to install straight out of the box
- ▶ Compact, requiring little space
- ▶ Hand held controller with WYSIWYG display
- ▶ Print head module with internal product sensor
- ▶ Lexmark™ Inkjet technology
- ▶ All-in-one print head and cartridge
- ▶ 42ml Ink cartridges are clean and easy to install
- ▶ Simple ink changeovers
- ▶ 300 or 600 dpi print resolution
- ▶ Low Ink LED Indicator
- ▶ Printer status display
- ▶ Line speeds up to 61 metres per minute
- ▶ Multi-language facility
- ▶ Breakaway print head module
- ▶ Add-on print head modules
- ▶ Top coding bracket
- ▶ Build in Data Flash Card slot for software upgrades
- ▶ No moving parts for maximum efficiency
- ▶ No PC required
- ▶ Networking Capabilities

CleanCode inkjet coders are low cost, low maintenance alternatives to CIJ, DOD and large character printers. They can be fitted directly to conveyors or packaging machinery or can be free standing using the optional floor stand.

OPEN  
DATE

OPEN  
DATE

World Class Coding & Marking Systems



getting you  
up to speed

# CleanCode EV1 & EV2 LX



## PRINthead MODULE



## HAND HELD CONTROLLER



## INKJET CARTRIDGES BY



### Ink Supply

Cartridge Volume: 42ml  
Porous Ink: Black

### Power Required

110-240 vAC, 50-60 Hz, 0.5A

### Environmental

10 to 40°C (50 to 104°F)  
Up to 80% RH non-condensing

## PHYSICAL DIMENSIONS

Controller: Width: 105mm, Depth: 38mm, Height: 222mm  
Printhead Module: Width: 64mm, Depth: 102mm, Height: 76mm

## SPECIFICATIONS

Hardware & Software Features	EV1 LX	EV2 LX
Hand held controller	Standard	Standard
Printhead module with internal product sensor	Standard	Standard
Mounting bracketry for side coding applications	Standard	Standard
Alpha /numeric character set with special characters	Standard	Standard
Ability to control up to 32 printheads via RS 485	Standard	Standard
Mixed raster printing	N/A	Standard
Character heights: 12.7mm in one line, 5.5mm in two lines	Standard	Standard
Character heights: 3.2mm in three lines, 2.4mm in four lines	N/A	Standard
Alternative font styles and character heights	Optional	Optional
Maximum number characters per line of text	24 (option to increase)	48
Storage of up to 100 messages in controller	Optional	Standard
Programmable line speed, print direction and print delay	Standard	Standard
Print message repeat	Optional	Standard
Inter-character spacing, inverted print	Standard	Standard
Variable time and date formats, sequential numbering, shift coding, date offset, automatic message repeat, password protection	Optional	Standard
Standard Barcodes Include: I 2 of 5, UPC-A, 128 B, EAN 8, Code 39, UPC-E, 128 C & EAN 13	Optional	Standard
EV-Net software for PC control of up to 32 printers	Optional	Optional
Multiple language prompts: English, Spanish, French & German	Standard	Standard

[www.inkjetcoder.com](http://www.inkjetcoder.com)

**PPMA**

**OPEN  
DATE**

**Open Date Equipment Ltd**  
Units 8 & 9 Puma Trade Park  
145 Morden Road  
Mitcham, Surrey, CR4 4DG.  
**UNITED KINGDOM**  
Tel: +44 (0)20 8655 4999  
Fax: +44 (0)20 8655 4990  
Email: sales@opendate.co.uk  
Web site: www.inkjetcoder.com

**Open Date Systems Inc**  
Springfield Road, PO Box 538  
Georges Mills, NH 03751  
**U.S.A.**  
Tel: +(1) 603 763 3444  
Fax: +(1) 603 763 4222  
Toll free: 877-OPENDATE  
Email: info@opendate.com  
Web site: www.inkjetcoder.com

**Open Date France**  
Z.I. D'Attichy  
60350 Attichy  
**France**  
Tel: +33 (0) 344 42 94 43  
Fax: +33 (0) 344 42 17 17  
Email: info@opendatefrance.com  
Web site: www.inkjetcoder.com

**Open Date GmbH**  
Mittlere Stämmig 4  
97297 Üttingen  
**Germany**  
Tel: +49 (0) 9369 98 24 0  
Fax: +49 (0) 9369 98 24 24  
Email: info@opendate.de  
Web site: www.inkjetcoder.com